

# **DecibeX Strong 200**

## Technical Data Sheet

<u>Material:</u>	Impact sound reducing underlay made from specially processed Polyester scrim for the application under floating PVC flooring (LVT)
<u>Thickness:</u>	0,93 mm (DIN EN ISO 9073-2) Tolerance +/- 15%
<u>Weight:</u>	200 g/m <sup>2</sup> Tolerance - 5%
<u>Dimensions:</u>	15 m <sup>2</sup> / roll: width 1 m / length: 15 m
<u>Roll weight:</u>	Approx. 3,5 kg
<u>Maximum tensile strength longit.:</u>	770 (N/50 mm) Tolerance -10%
<u>Maximum tensile strength transv.:</u>	530 (N/50 mm) Tolerance -10%
<u>Elongation at break longit.:</u>	29 % Tolerance -15%
<u>Elongation at break transv.:</u>	33 % Tolerance -15%
<u>Color:</u>	Green
<u>Impact sound reduction:</u>	$\Delta Lw = 19 \text{ dB}$ under 4 mm PVC LVT in floating installation EN ISO 10140-1
<u>Suitable for underfloor heating:</u>	Yes
<u>Storage:</u>	Cool and dry, stored upright. Avoid direct sunlight.



**automotive insulations**  
PROVIDING SOUND SOLUTIONS  
PART OF THE AUTINS GROUP



+44 (0)1788 578300



+44 (0)1788 579700



admin@autins.co.uk

Automotive Insulations, Central Point One, Central Park Drive, Rugby, Warwickshire, CV23 0WE

Registration Number: 875424 VAT No: GB892218311